

Technical Datasheet

Magna Dental Model



Phot**O**centric





Magna Platform pictured shows 48 x Aligner Models

Photocentric Magna Dental Model Beige has been specially created for 3D printing highly detailed and accurate dental models. It provides outstanding accuracy with at least 90% of scanned models within ±100µm tolerance, perfect for Aligner Dental Model production. Using Magna Dental Model Beige ensures a dry surface finish, accurate detail and great mechanical stiffness, shorter print and post process cycles with a high Shore hardness of 84D.

Optimised for:

 Orthodontic models for clear aligner manufacture Thermoforming

Study, opposing and denture base models

Unique features:



Easy to print and post process

High accuracy



Magna Dental Model Properties

| Tensile Properties | | |
|--------------------------------|----------------|------------------------------|
| Tensile Modulus * | 2750 MPa | ASTM D638 |
| Ultimate Tensile Strength * | 56 MPa | ASTM D638 |
| Elongation at break * | 2.7% | ASTM D638 |
| Flexural Properties | | |
| Flexural Modulus * | 2570 MPa | ASTM D790 |
| Flexural Strength * | 84 MPa | ASTM D790 |
| Impact Properties | | |
| Impact Strength Notched Izod * | 19.5 J/m | ASTM D256 |
| Impact Strength Notched Izod * | 2.5 kJ/m2 | ISO 180 |
| General Properties | | |
| Shore Hardness * | 84 Shore D | ASTM D2240 |
| Water Absorption (Short Term) | 0.13% | ASTM D570 |
| Viscosity | 150 cPs | At 25°C Brookfield spindle 3 |
| Density | 1.10 g/cm3 | |
| Storage | 10 <t>50°C</t> | |
| Biocompatibility | | |
| Cytotoxicity* | Passed | ISO 10993-5 |

* Mechanical properties stated based on fully cured material.

We are constantly reviewing and improving our range of high-performance materials. For the very latest information, please visit the Photocentric website



- 1. To print with Photocentric Liquid Crystal Magna, choose 'Dental Model Beige' and the desired layer thickness when preparing your print file in Photocentric Studio.
- 2. Heat the resin to 30°C in the bottle.
- 3. Shake the resin bottle for 2 minutes before pouring into the resin vat.



Post-Print Instructions

- 1. Parts can be washed in 15 minutes using Photocentric Resin Cleaner or alternatively, in 10 minutes using Photocentric Resin Cleaner 30.
- 2. Once washed, rinse with warm water for 2 minutes
- 3. Dry with compressed air to remove any remaining water. Or alternatively, leave to air-dry.
- 4. Place the platform into the Photocentric Cure L2 for a minimum of 60 minutes at 60°C or until parts are fully cured.
- 5. Remove the platform from the Cure L2 and immediately submerge in cold water for thermal shocking. Parts can be removed from the platform with minimal effort.
- 6. It is recommended to clean the resin vat after each print job as pigments may settle.



