

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form	: Mixture
Trade name	: HighTemp DL400
Type of product	: Photocentric Daylight 3D Resin
Other means of identification	: DAYHTMAM05

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Main use category	: Industrial use, Professional use, Consumer use
Use of the substance/mixture	: For use in Photocentric Daylight Printers

#### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

#### Supplier

Photocentric Ltd  
Titan House  
20 Titan Drive  
Peterborough, PE1 5XN - United Kingdom  
T +44 (0) 1733 349937 (UK Office hours only)  
[info@photocentric.co.uk](mailto:info@photocentric.co.uk) - <https://photocentricgroup.com/>

#### Distributor

Photocentric Inc  
855 N. 107th Ave  
Suite A110  
85323 Avondale, Arizona - United States  
T 006235813220 x1009 (USA Office hours only)  
[customerservice@photocentricusa.com](mailto:customerservice@photocentricusa.com) - <https://photocentricgroup.com/>

### 1.4. Emergency telephone number

Emergency number	: +44 (0) 1733 349937 (UK Office hours only) 006235813220 x1009 (USA Office hours only) Transport Emergencies for US & CANADA: For Hazardous Materials [or Dangerous Goods] Incident Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC 1-800-424-9300 / +1 703-527-3887 CCN 992854
------------------	--

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 1	H318
Skin sensitisation, Category 1	H317
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411
Full text of H- and EUH-statements: see section 16	

#### Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

# HighTemp DL400

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Contains	: Proprietary (Aliphatic urethane methacrylate); Proprietary (Crosslinking agent); Proprietary (Photoinitiator)
Hazard statements (CLP)	: H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H318 - Causes serious eye damage. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P261 - Avoid breathing fume, mist, spray, vapours.vapours, fume, spray. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear eye protection, protective clothing, protective gloves. P302+P352 - IF ON SKIN: Wash with plenty of soap and water. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a doctor. P321 - Specific treatment (see supplemental first aid instruction on this label). P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

### 2.3. Other hazards

Other hazards which do not result in classification : None under normal conditions.

Contains no PBT and/or vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Proprietary (Triacrylate)	$\geq 25 - < 70$	Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Proprietary (Diacylate)	$\geq 25 - < 50$	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317
Proprietary (Aliphatic urethane methacrylate)	$\geq 10 - < 15$	Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Proprietary (Diacylate)	$\geq 10 - < 15$	Skin Irrit. 2, H315 Eye Irrit. 2, H319
Proprietary (Photoinitiator)	$\geq 1 - < 3$	Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Proprietary (Crosslinking agent)	$\geq 0.1 - < 1$	Eye Irrit. 2, H319 Skin Sens. 1, H317
Proprietary (Photoinitiator)	$\geq 0.1 - < 1$	Flam. Sol. 1, H228 Repr. 2, H361f STOT RE 2, H373 Aquatic Chronic 2, H411
Proprietary (Crosslinking agent)	$< 1$	Acute Tox. 4 (Oral), H302 STOT RE 2, H373 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)

Full text of H- and EUH-statements: see section 16

# HighTemp DL400

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell. Never give anything by mouth to an unconscious person.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or a doctor. Apply artificial respiration if victim is not breathing.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash skin with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention if you feel unwell.
First-aid measures after ingestion	: If swallowed, seek medical advice immediately and show this container or label. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Rinse mouth out with water. Get medical advice/attention if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Inhalation may cause irritation (cough, short breathing, difficulty in breathing). May cause respiratory irritation.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Risk of serious damage to eyes. Serious damage to eyes.
Symptoms/effects after ingestion	: Harmful if swallowed. May cause irritation to the digestive tract.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. In all cases of doubt, or when symptoms persist, seek medical attention. Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

#### 5.3. Advice for firefighters

Precautionary measures fire	: Keep cool. Protect from sunlight.
Firefighting instructions	: Do not enter fire area without proper protective equipment, including respiratory protection. Fight fire from safe distance and protected location. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: High temperature decomposition products are harmful by inhalation.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene. For further information refer to section 8: "Exposure controls/personal protection". Avoid breathing mist, spray, vapours.

# HighTemp DL400

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. Protective gloves. Safety glasses. Self-contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Ventilate area.

### 6.2. Environmental precautions

Avoid release to the environment. Prevent liquid from entering sewers, watercourses, underground or low areas. Very toxic to aquatic life with long lasting effects.

### 6.3. Methods and material for containment and cleaning up

For containment	: For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Collect spillage.
Methods for cleaning up	: Take up liquid spill into absorbent material. This material and its container must be disposed of in a safe way, and as per local legislation.
Other information	: Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling	: Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing fume, mist, spray, vapours.
Handling temperature	: < 50 °C
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Store in a well-ventilated place. Keep cool.
Incompatible materials	: Direct sunlight.
Storage temperature	: < 50 °C
Storage area	: Store in a well-ventilated place. Store away from heat.
Special rules on packaging	: Store in a closed container.
Packaging materials	: Do not store in corrodable metal. Store always product in container of same material as original container.

### 7.3. Specific end use(s)

The identified uses for this product are detailed in section 1.2.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

No additional information available

### 8.2. Exposure controls

#### Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure good ventilation of the work station.

#### Personal protective equipment:

Wear recommended personal protective equipment. Gloves. Safety glasses.

# HighTemp DL400

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Materials for protective clothing:

Wear suitable protective clothing and gloves

### Eye protection:

Safety glasses

### Skin and body protection:

Wear suitable protective clothing

### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

### Personal protective equipment symbol(s):



### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: dark orange.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 600 – 700 mPa·s @25°C
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

# HighTemp DL400

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Stable under normal conditions of use.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

#### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### Proprietary (Aliphatic urethane methacrylate) (72869-86-4)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg bw/day
LC50 Inhalation - Rat (Dust/Mist)	> 5 mg/l/4h

#### Proprietary (Diacylate) (52404-33-8)

LD50 oral rat	> 2000 mg/kg
---------------	--------------

#### Proprietary (Crosslinking agent) (28961-43-5)

LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: EU Method B.1 (Acute Toxicity (Oral))
LD50 dermal rabbit	> 13200 mg/kg bodyweight Animal: rabbit

#### Proprietary (Crosslinking agent) (7575-23-7)

LD50 oral rat	1000 – 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LC50 Inhalation - Rat	> 3.363 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)

#### Proprietary (Photoinitiator) (162881-26-7)

LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: EU Method B.1 (Acute Toxicity (Oral))
---------------	---

# HighTemp DL400

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: other:92/69/EEC
-----------------	---

<b>Proprietary (Photoinitiator) (125051-32-3)</b>	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: other:OECD GUIDELINE No.401 (CORRESPONDING TO 84/449/EEC, B.1)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: other:OECD GUIDELINE No.402 (CORRESPONDING TO 84/449/EEC, B.3)

<b>Proprietary (Triacrylate) (40220-08-4)</b>	
LD50 oral rat	No mortality/Rat: 2.000 mg/kg (Method: OECD Test Guideline 423)

<b>Proprietary (Diacrylate) (57472-68-1)</b>	
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

<b>Proprietary (Crosslinking agent) (28961-43-5)</b>	
NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

<b>Proprietary (Crosslinking agent) (7575-23-7)</b>	
NOAEL (oral, rat, 90 days)	≥ 100 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

<b>Proprietary (Photoinitiator) (162881-26-7)</b>	
NOAEL (oral, rat, 90 days)	> 1000 mg/kg bodyweight Animal: rat, Guideline: other:92/69/eec

<b>Proprietary (Photoinitiator) (125051-32-3)</b>	
NOAEL (oral, rat, 90 days)	< 10.8 mg/kg bodyweight Animal: other:ALBINO RAT/Tif: RAIf (SPF) HYBRIDIS OF RII/1×RII/2, Guideline: other:EEC Directive, B.7

<b>Proprietary (Triacrylate) (40220-08-4)</b>	
LOAEL (oral, rat, 90 days)	100 mg/kg bodyweight/day (Method: OECD Test Guideline 422, Rat, 28 d)
NOAEL (oral, rat, 90 days)	50 mg/kg bodyweight/day By oral route: Local irritation, NOAEL (Method: OECD Test Guideline 422, Rat, 28 d)

# HighTemp DL400

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Proprietary (Diacrylate) (57472-68-1)

NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
----------------------------	---

Aspiration hazard : Not classified

Potential adverse human health effects and symptoms : Irritation: severely irritant to eyes. Harmful in contact with skin. Harmful if swallowed.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

Not rapidly degradable

### Proprietary (Aliphatic urethane methacrylate) (72869-86-4)

LC50 - Fish [1]	≥ 10.1 mg/l Zebra Fish (Brachydanio rerio)
EC50 - Crustacea [1]	> 1200 µg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 0.68 mg/l
NOEC chronic algae	0.21 mg/l Green Algae (Desmodesmus subspicatus)

### Proprietary (Crosslinking agent) (28961-43-5)

LC50 - Fish [1]	1.95 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	70.7 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	2.2 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

### Proprietary (Crosslinking agent) (7575-23-7)

LC50 - Fish [1]	0.034 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 0.35 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 0.12 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

### Proprietary (Photoinitiator) (162881-26-7)

LC50 - Fish [1]	> 0.09 mg/l Test organisms (species): other:Zebra Fish Brachydanio rerio
EC50 - Crustacea [1]	> 1.175 mg/l Test organisms (species): other aquatic crustacea:Daphnia Magna
EC50 72h - Algae [1]	> 0.26 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

### Proprietary (Photoinitiator) (125051-32-3)

LC50 - Fish [1]	> 100 mg/l Test organisms (species): other:ZEBRA FISH
EC50 - Other aquatic organisms [1]	2.15 mg/l Test organisms (species): other aquatic crustacea:DM



# HighTemp DL400

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Proprietary (Triacrylate) (40220-08-4)	
LC50 - Fish [1]	9.43 mg/l (Danio rerio (zebra fish)) (Method: OECD Test Guideline 203)
EC50 - Crustacea [1]	158.3 mg/l (Method: OECD Test Guideline 202)EC50, 48 h (Daphnia magna (Water flea))
EC50 72h - Algae [1]	25.7 mg/l Pseudokirchneriella subcapitata (green algae) I (Method: OECD Test Guideline 201)
ErC50 other aquatic plants	12.9 mg/l ErC10, 72 h (Pseudokirchneriella subcapitata (green algae)) : (Method: OECD Test Guideline 201)
NOEC (chronic)	≥ 100 mg/l NOEC, 14 d (Activated sludge)(Respiration inhibition)

Proprietary (Diacrylate) (57472-68-1)	
LC50 - Fish [1]	2.2 – 4.64 mg/l Test organisms (species): Leuciscus idus
EC50 - Crustacea [1]	22.3 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	16.7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

### 12.2. Persistence and degradability

Proprietary (Aliphatic urethane methacrylate) (72869-86-4)	
Persistence and degradability	Not established.
Biodegradation	22 % CO2 Evolution: Modified Sturm (OECD 301B)

Proprietary (Photoinitiator) (125051-32-3)	
Persistence and degradability	Biodegradability in water: no data available.

Proprietary (Triacrylate) (40220-08-4)	
Persistence and degradability	May cause long-term adverse effects in the environment.
Biodegradation	14.5 – 19.7 % after 28 d (Method: OECD Test Guideline 301 F)

### 12.3. Bioaccumulative potential

Proprietary (Aliphatic urethane methacrylate) (72869-86-4)	
Partition coefficient n-octanol/water (Log Pow)	3.39
Bioaccumulative potential	No bioaccumulation data available.

Proprietary (Triacrylate) (40220-08-4)	
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.61 25 °C (OECD Test Guideline 117)

### 12.4. Mobility in soil

Proprietary (Triacrylate) (40220-08-4)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.79 ( Method: calculated ) Absorption / desorption:

### 12.5. Results of PBT and vPvB assessment

Component	
Proprietary (Aliphatic urethane methacrylate) (72869-86-4)	PBT: not relevant – no registration required

# HighTemp DL400

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Proprietary (Diacrylate) (52404-33-8)

PBT: not relevant – no registration required

### 12.6. Other adverse effects

No additional information available






## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Avoid release to the environment. Comply with applicable regulations for solid waste disposal. Dispose in a safe manner in accordance with local/national regulations.
Additional information	: Clean up even minor leaks or spills if possible without unnecessary risk.
Ecological information	: Avoid release to the environment.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082
<b>14.2. UN proper shipping name</b>				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Dipropylene Glycol Diacrylate ; Tris(2-hydroxyethyl) Isocyanurate Triacrylate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Dipropylene Glycol Diacrylate ; Tris(2-hydroxyethyl) Isocyanurate Triacrylate)	Environmentally hazardous substance, liquid, n.o.s. (Dipropylene Glycol Diacrylate ; Tris(2-hydroxyethyl) Isocyanurate Triacrylate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Dipropylene Glycol Diacrylate ; Tris(2-hydroxyethyl) Isocyanurate Triacrylate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Dipropylene Glycol Diacrylate ; Tris(2-hydroxyethyl) Isocyanurate Triacrylate)
<b>Transport document description</b>				
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Dipropylene Glycol Diacrylate ; Tris(2-hydroxyethyl) Isocyanurate Triacrylate), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Dipropylene Glycol Diacrylate ; Tris(2-hydroxyethyl) Isocyanurate Triacrylate), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Dipropylene Glycol Diacrylate ; Tris(2-hydroxyethyl) Isocyanurate Triacrylate), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Dipropylene Glycol Diacrylate ; Tris(2-hydroxyethyl) Isocyanurate Triacrylate), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Dipropylene Glycol Diacrylate ; Tris(2-hydroxyethyl) Isocyanurate Triacrylate), 9, III
<b>14.3. Transport hazard class(es)</b>				
9	9	9	9	9
				
<b>14.4. Packing group</b>				
III	III	III	III	III

# HighTemp DL400

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 14.5. Environmental hazards

Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: M6
Special provisions (ADR)	: 274, 335, 375, 601
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBV
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV13
Hazard identification number (Kemler No.)	: 90
Orange plates	:



Tunnel restriction code (ADR)	: -
EAC code	: •3Z

#### Transport by sea

Special provisions (IMDG)	: 274, 335, 969
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: LP01, P001
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-F
Stowage category (IMDG)	: A

#### Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y964
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 964
PCA max net quantity (IATA)	: 450L
CAO packing instructions (IATA)	: 964
CAO max net quantity (IATA)	: 450L
Special provisions (IATA)	: A97, A158, A197, A215
ERG code (IATA)	: 9L

#### Inland waterway transport

Classification code (ADN)	: M6
Special provisions (ADN)	: 274, 335, 375, 601
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Equipment required (ADN)	: PP
Number of blue cones/lights (ADN)	: 0

# HighTemp DL400

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Rail transport

Classification code (RID)	: M6
Special provisions (RID)	: 274, 335, 375, 601
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1, TP29
Tank codes for RID tanks (RID)	: LGBV
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Special provisions for carriage - Loading, unloading and handling (RID)	: CW13, CW31
Colis express (express parcels) (RID)	: CE8
Hazard identification number (RID)	: 90

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)  
Contains no substance(s) listed on the REACH Candidate List  
Contains no substance(s) listed on REACH Annex XIV (Authorisation List)  
Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)  
Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

#### 15.1.2. National regulations

##### Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG)  
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG)  
Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)  
Hazardous Incident Ordinance (12. BImSchV) : Is not subject to the Hazardous Incident Ordinance (12. BImSchV)

##### Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed  
SZW-lijst van mutagene stoffen : None of the components are listed  
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed  
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : PI-784 is listed  
SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

##### Denmark

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product  
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
-----	---

# HighTemp DL400

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

### Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Sol. 1	Flammable solids, Category 1
H228	Flammable solid.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.

# HighTemp DL400

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2

SDS EU (REACH Annex II) Photocentric Amended

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.