

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Trade name : Flexible DL220 - Black
 Other means of identification : MAGFLBK05

1.2. Recommended use and restrictions on use

Use of the substance/mixture : For use in Photocentric Daylight Printers

1.3. Supplier

Supplier

Photocentric Ltd
 Titan House
 20 Titan Drive
 Peterborough, PE1 5XN - United Kingdom
 T +44 (0) 1733 349937 (UK Office hours only)
info@photocentric.co.uk - <https://photocentricgroup.com/>

Distributor

Photocentric Inc
 855 N. 107th Ave
 Suite A110
 Avondale, Arizona 85323 - United States
 T 006235813220 x1009 (USA Office hours only)
customerservice@photocentricusa.com - <https://photocentricgroup.com/>

1.4. Emergency telephone number

Emergency number : +44 (0) 1733 349937 (UK Office hours only)
 006235813220 x1009 (USA Office hours only)

Transport Emergencies for US & CANADA: For Hazardous Materials [or Dangerous Goods]
 Incident Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC 1-800-424-9300 / +1 703-527-3887 CCN 992854

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Hazardous to the aquatic environment – Acute Hazard Category 3	H402	Harmful to aquatic life
Hazardous to the aquatic environment – Chronic Hazard Category 1	H410	Very toxic to aquatic life with long lasting effects

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning
 Hazard statements (GHS US) : H402 - Harmful to aquatic life
 H410 - Very toxic to aquatic life with long lasting effects
 Precautionary statements (GHS US) : P273 - Avoid release to the environment.
 P391 - Collect spillage.
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

Flexible DL220 - Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Conc. (% w/w)	GHS US classification
Proprietary (Acrylate)	≥ 25 – < 50	Aquatic Chronic 1, H410
Proprietary (Acrylate)	≥ 10 – < 20	Aquatic Acute 2, H401
Proprietary (Photoinitiator)	≥ 3 – < 5	Aquatic Chronic 1, H410
Proprietary (Crosslinking agent)	≥ 0.1 – < 1	Acute Tox. 4 (Oral), H302 STOT RE 2, H373
Proprietary (Photoinitiator) (Note T)	< 0.1	STOT RE 2, H373
Proprietary (Inhibitor)	< 0.1	Acute Tox. 4 (Oral), H302

Note T - This substance may be marketed in a form which does not have the physical hazards as indicated by the classification in the entry in Part 3. If the results of the relevant method or methods in accordance with Part 2 of Annex I of this Regulation show that the specific form of substance marketed does not exhibit this physical property or these physical hazards, the substance shall be classified in accordance with the result or results of this test or these tests. Relevant information, including reference to the relevant test method(s) shall be included in the safety data sheet.

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. Seek medical attention immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash skin with plenty of water.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell. Rinse mouth out with water. If swallowed, seek medical advice immediately and show this container or label. Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms	: Harmful if swallowed. May be harmful in contact with skin.
Symptoms/effects	: May be harmful if inhaled. May cause an allergic skin reaction. May be harmful if swallowed and enters airways.
Symptoms/effects after inhalation	: Inhalation may cause irritation (cough, short breathing, difficulty in breathing).
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Harmful if swallowed. May cause irritation to the digestive tract.
Chronic symptoms	: Suspected of damaging fertility. Suspected of damaging the unborn child.

Flexible DL220 - Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically. Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure. In all cases of doubt, or when symptoms persist, seek medical attention. Seek medical advice (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

- Fire hazard : In case of fire, irritating fumes come free.
- Explosion hazard : No direct explosion hazard.
- Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

- Precautionary measures fire : Evacuate area. This product is not to be used under conditions of poor ventilation. Keep cool. Protect from sunlight. Store in tightly closed, properly ventilated containers away from heat, sparks, open flame.
- Firefighting instructions : Do not enter fire area without proper protective equipment, including respiratory protection. Evacuate area. Exercise caution when fighting any chemical fire.
- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
- Other information : High temperature decomposition products are harmful by inhalation.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.

6.1.1. For non-emergency personnel

- Protective equipment : Wear recommended personal protective equipment. Wear suitable respiratory protection (conforming to EN140 with Type A filter or better) and gloves (type EN374) if regular skin contact likely.
- Emergency procedures : See section 8 of the SDS for more information on personal protective equipment. Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. Wear recommended personal protective equipment. Self-contained breathing apparatus. Safety glasses. Protective gloves. For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Evacuate unnecessary personnel. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Ventilate area. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment. Prevent liquid from entering sewers, watercourses, underground or low areas.

6.3. Methods and material for containment and cleaning up

- For containment : For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Collect spillage. Stop leak, if possible without risk.
- Methods for cleaning up : Take up liquid spill into absorbent material. This material and its container must be disposed of in a safe way, and as per local legislation.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

Flexible DL220 - Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautions for safe handling	: Ensure good ventilation of the work station. Wear personal protective equipment. Ensure that there is a suitable ventilation system. Do not handle in a confined space. Avoid contact with skin, eyes and clothing. Protective clothing (with elasticated cuffs and closed neck). Do not breathe vapors. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
Handling temperature	: 10 – 50 °C
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight.
Incompatible materials	: Direct sunlight.
Storage temperature	: < 50 °C
Packaging materials	: Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Flexible DL220 - Black	
No additional information available	
Proprietary (Acrylate) (48145-04-6)	
No additional information available	
Proprietary (Photoinitiator) (125051-32-3)	
No additional information available	
Proprietary (Photoinitiator) (162881-26-7)	
No additional information available	
Proprietary (Crosslinking agent) (7575-23-7)	
No additional information available	
Proprietary (Inhibitor) (150-76-5)	
USA - ACGIH - Occupational Exposure Limits	
Local name	4-Methoxyphenol
ACGIH OEL TWA	5 mg/m ³
Remark (ACGIH)	TLV® Basis: Eye irr; skin dam
Regulatory reference	ACGIH 2024
Proprietary (Acrylate) (5888-33-5)	
No additional information available	

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wear a respirator conforming to EN140 with Type A filter or better.

Materials for protective clothing:

Wear suitable protective clothing and gloves. Nitrile rubber. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

Hand protection:

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Nitrile-rubber protective gloves

Eye protection:

Safety glasses (EN 166). Chemical goggles or safety glasses. Safety glasses

Flexible DL220 - Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin and body protection:

Wear chemically protective gloves, lab coat or apron to prevent prolonged or repeated skin contact. Wear suitable protective clothing. Protective clothing (EN 14605 or EN 13034)

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Wear suitable respiratory protection (conforming to EN140 with Type A filter or better) and gloves (type EN374) if regular skin contact likely.

Personal protective equipment symbol(s):



Thermal hazard protection:

Typical measures to maintain workplace concentrations of airborne VOCs and particulates below respective OELs: e.g. thermal wet scrubber – gas removal and/or air filtration – particle removal and/or thermal oxidation and/or vapour recovery – adsorption.

Other information:

Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: Black
Odor	: characteristic
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: > 100 The product has not been tested. The statements are based on the properties of the individual components.
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability	: No data available
Vapor pressure	: 0.133 @25 °C. The product has not been tested. The statements are based on the properties of the individual components.
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
No data available	Viscosity, kinematic : No data available
Viscosity, dynamic	: 3770 mPa·s
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

Flexible DL220 - Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Protect from sunlight.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Proprietary (Acrylate) (48145-04-6)	
LD50 oral rat	5000 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
ATE US (oral)	5000 mg/kg body weight

Proprietary (Photoinitiator) (125051-32-3)	
LD50 oral rat	> 2000 mg/kg body weight Animal: rat, Guideline: other:OECD GUIDELINE No.401 (CORRESPONDING TO 84/449/EEC, B.1)
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: other:OECD GUIDELINE No.402 (CORRESPONDING TO 84/449/EEC, B.3)

Proprietary (Photoinitiator) (162881-26-7)	
LD50 oral rat	> 2000 mg/kg body weight Animal: rat, Guideline: EU Method B.1 (Acute Toxicity (Oral))
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: other:92/69/EEC

Proprietary (Crosslinking agent) (7575-23-7)	
LD50 oral rat	1000 – 2000 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LC50 Inhalation - Rat	> 3.363 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)
ATE US (oral)	1000 mg/kg body weight

Proprietary (Inhibitor) (150-76-5)	
LD50 oral rat	1600 mg/kg Source: HSDB, ChemIDplus, NITE
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: other:OECD No 423 Acute Oral Toxicity – Acute Toxic Class Method
ATE US (oral)	1600 mg/kg body weight

Proprietary (Acrylate) (5888-33-5)	
LD50 dermal rabbit	> 3000 mg/kg body weight Animal: rabbit, Animal sex: male, Guideline: other:

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

Flexible DL220 - Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

STOT-repeated exposure : Not classified

Proprietary (Photoinitiator) (125051-32-3)	
NOAEL (oral,rat,90 days)	< 10.8 mg/kg body weight Animal: other:ALBINO RAT/Tif: RAIf (SPF) HYBRIDIS OF RII/1×RII/2, Guideline: other:EEC Directive, B.7
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Proprietary (Photoinitiator) (162881-26-7)	
NOAEL (oral,rat,90 days)	> 1000 mg/kg body weight Animal: rat, Guideline: other:92/69/eec
Proprietary (Crosslinking agent) (7575-23-7)	
NOAEL (oral,rat,90 days)	≥ 100 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Proprietary (Inhibitor) (150-76-5)	
LOAEL (oral,rat,90 days)	300 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:EPA OPPTS 870.3650 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (oral,rat,90 days)	150 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:EPA OPPTS 870.3650 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Aspiration hazard : Not classified

Viscosity, kinematic : No data available

Potential Adverse human health effects and symptoms : Harmful if swallowed. May be harmful in contact with skin.

Symptoms/effects : May be harmful if inhaled. May cause an allergic skin reaction. May be harmful if swallowed and enters airways.

Symptoms/effects after inhalation : Inhalation may cause irritation (cough, short breathing, difficulty in breathing).

Symptoms/effects after skin contact : None under normal conditions.

Symptoms/effects after eye contact : Causes serious eye damage.

Symptoms/effects after ingestion : Harmful if swallowed. May cause irritation to the digestive tract.

Chronic symptoms : Suspected of damaging fertility. Suspected of damaging the unborn child.

Other information : Likely routes of exposure: inhalation. Likely routes of exposure: ingestion, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Very toxic to aquatic life with long lasting effects. Harmful to aquatic life.

Ecology - water : Toxic to aquatic life with long lasting effects.

Proprietary (Acrylate) (48145-04-6)	
LC50 - Fish [1]	≈ 10 mg/l Test organisms (species): Leuciscus idus
EC50 - Crustacea [1]	1.21 mg/l Test organisms (species): Daphnia magna
Proprietary (Photoinitiator) (125051-32-3)	
LC50 - Fish [1]	> 100 mg/l Test organisms (species): other:ZEBRA FISH
EC50 - Other aquatic organisms [1]	2.15 mg/l Test organisms (species): other aquatic crustacea:DM
Proprietary (Photoinitiator) (162881-26-7)	
LC50 - Fish [1]	> 0.09 mg/l Test organisms (species): other:Zebra Fish Brachydanio rerio
EC50 - Crustacea [1]	> 1.175 mg/l Test organisms (species): other aquatic crustacea:Daphnia Magna
Proprietary (Crosslinking agent) (7575-23-7)	
LC50 - Fish [1]	0.034 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 0.35 mg/l Test organisms (species): Daphnia magna
Proprietary (Inhibitor) (150-76-5)	
LC50 - Fish [1]	28.5 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	3 mg/l Test organisms (species): Daphnia magna

Flexible DL220 - Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proprietary (Inhibitor) (150-76-5)	
ErC50 algae	54.7 mg/l Source: EHCA
LOEC (chronic)	> 1.45 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.68 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Proprietary (Acrylate) (5888-33-5)	
LC50 - Fish [1]	0.704 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
LOEC (chronic)	0.277 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.092 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

Proprietary (Photoinitiator) (125051-32-3)	
Persistence and degradability	Biodegradability in water: no data available.

12.3. Bioaccumulative potential

Proprietary (Inhibitor) (150-76-5)	
Partition coefficient n-octanol/water (Log Pow)	1.23 Source: ECHA

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Avoid release to the environment. Comply with applicable regulations for solid waste disposal. Dispose in a safe manner in accordance with local/national regulations. Disposal must be done according to official regulations.
Additional information	: Clean up even minor leaks or spills if possible without unnecessary risk. Consult an expert on waste disposal or treatment. Do not re-use empty containers.
Ecological waste information	: Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated

Transportation of Dangerous Goods

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Flexible DL220 - Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

Flexible DL220 - Black

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Proprietary (Acrylate)	CAS-No. 48145-04-6	≥ 10 – < 20%
Proprietary (Photoinitiator)	CAS-No. 125051-32-3	< 0.1%
Proprietary (Photoinitiator)	CAS-No. 162881-26-7	≥ 3 – < 5%
Proprietary (Crosslinking agent)	CAS-No. 7575-23-7	≥ 0.1 – < 1%
Proprietary (Inhibitor)	CAS-No. 150-76-5	< 0.1%
Proprietary (Acrylate)	CAS-No. 5888-33-5	≥ 25 – < 50%

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Proprietary (Photoinitiator) (125051-32-3)

EPA TSCA Regulatory Flag PMN - PMN - indicates a commenced PMN substance.

Proprietary (Photoinitiator) (162881-26-7)

EPA TSCA Regulatory Flag PMN - PMN - indicates a commenced PMN substance.

15.2. International regulations

CANADA

Proprietary (Acrylate) (48145-04-6)

Listed on the Canadian DSL (Domestic Substances List)

Proprietary (Photoinitiator) (125051-32-3)

Listed on the Canadian NDSL (Non-Domestic Substances List)

Proprietary (Photoinitiator) (162881-26-7)

Listed on the Canadian DSL (Domestic Substances List)

Proprietary (Crosslinking agent) (7575-23-7)

Listed on the Canadian DSL (Domestic Substances List)

Proprietary (Inhibitor) (150-76-5)

Listed on the Canadian DSL (Domestic Substances List)

Proprietary (Acrylate) (5888-33-5)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Proprietary (Acrylate) (48145-04-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Proprietary (Photoinitiator) (125051-32-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Proprietary (Photoinitiator) (162881-26-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Proprietary (Crosslinking agent) (7575-23-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Proprietary (Inhibitor) (150-76-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Proprietary (Acrylate) (5888-33-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Flexible DL220 - Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 04/09/2024

Full text of hazard classes and H-statements:

H302	Harmful if swallowed
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects

SDS US (GHS HazCom 2012) No CAS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.