

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 14/02/2022 Revision date: 17/04/2025 Supersedes: 14/02/2022 Version: 2.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Trade name : Elastic DL160 - Black

1.2. Other means of identification

Other means of identification : MAGELBK05

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : For use in Photocentric Daylight Printers

1.4. Supplier's details

Manufacturer

Photocentric Ltd
Titan House
20 Titan Drive
Peterborough, PE1 5XN, Cambridgeshire
United Kingdom
T +44 (0) 1733 349937 (UK Office hours only)
info@photocentric.co.uk - <https://photocentricgroup.com/>

1.5. Emergency phone number

Emergency number : +44 (0) 1733 349937 (UK Office hours only) 006235813220
x1009 (USA Office hours only)

Transport Emergencies for US & CANADA: For Hazardous Materials [or Dangerous Goods]
Incident Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC 1-800-424-9300 / +1 703-527-3887 CCN 992854

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Carcinogenicity, Category 2	H351	Suspected of causing cancer.
Hazardous to the aquatic environment — Chronic Hazard, Category 1	H410	Very toxic to aquatic life with long lasting effects.
Full text of H statements : see section 16		

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US) : Warning
Hazard statements (GHS US) : H351 - Suspected of causing cancer.
H410 - Very toxic to aquatic life with long lasting effects
Precautionary statements (GHS US) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P273 - Avoid release to the environment.

Elastic DL160 - Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P391 - Collect spillage.

P405 - Store locked up.

P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Conc. (% w/w)	GHS US classification
Proprietary (Acrylate)	≥ 25	Aquatic Chronic 1, H410
Proprietary (Acrylate) (Note D)	≥ 5 – < 10	Carc. 2, H351
Proprietary (Photoinitiator) (Note T)	≥ 0.1 – < 1	STOT RE 2, H373 Aquatic Chronic 2, H411
Proprietary (Crosslinking agent)	< 1	Acute Tox. 4 (Oral), H302 STOT RE 2, H373 Aquatic Chronic 1, H410

Note D: Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the words 'non-stabilised'.

Note T: This substance may be marketed in a form which does not have the physical hazards as indicated by the classification in the entry in Part 3. If the results of the relevant method or methods in accordance with Part 2 of Annex I of this Regulation show that the specific form of substance marketed does not exhibit this physical property or these physical hazards, the substance shall be classified in accordance with the result or results of this test or these tests. Relevant information, including reference to the relevant test method(s) shall be included in the safety data sheet.

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. Seek medical attention immediately. IF exposed or concerned: Get medical advice/attention.

Elastic DL160 - Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell. Rinse mouth out with water. If swallowed, seek medical advice immediately and show this container or label. Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Potential Adverse human health effects and symptoms	: Harmful if swallowed. May be harmful in contact with skin.
Symptoms/effects	: May be harmful if inhaled. May be harmful in contact with skin. May cause an allergic skin reaction.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: May cause slight irritation.
Symptoms/effects after ingestion	: May be harmful if swallowed.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically. Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure. In all cases of doubt, or when symptoms persist, seek medical attention. Seek medical advice (show the label where possible).
-----------------------------------	--

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: In case of fire, irritating fumes come free.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Precautionary measures fire	: Evacuate area. This product is not to be used under conditions of poor ventilation. Keep cool. Protect from sunlight. Store in tightly closed, properly ventilated containers away from heat, sparks, open flame.
Firefighting instructions	: Do not enter fire area without proper protective equipment, including respiratory protection. Evacuate area. Exercise caution when fighting any chemical fire.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: High temperature decomposition products are harmful by inhalation.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment. Wear suitable respiratory protection (conforming to EN140 with Type A filter or better) and gloves (type EN374) if regular skin contact likely.
----------------------	---

Elastic DL160 - Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Emergency procedures : See section 8 of the SDS for more information on personal protective equipment. Only qualified personnel equipped with suitable protective equipment may intervene. No open flames, no sparks, and no smoking. Do not breathe spray, vapors, mist.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Wear recommended personal protective equipment. Self-contained breathing apparatus. Safety glasses. Protective gloves. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Ventilate area.

Environmental precautions : Avoid release to the environment. Prevent liquid from entering sewers, watercourses, underground or low areas.

6.2. Methods and materials for containment and cleaning up

For containment : For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. This material and its container must be disposed of in a safe way, and as per local legislation. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

For further information refer to section 8: "Exposure controls/personal protection", For further information refer to section 13

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe vapors, spray, mist. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with skin and eyes.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

Handling temperature : 10 – 50 °C

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Incompatible materials : Direct sunlight.

Storage temperature : < 50 °C

Specific end uses : Data not available.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

No additional information available

Elastic DL160 - Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wear a respirator conforming to EN140 with Type A filter or better.

Materials for protective clothing:

Wear suitable protective clothing and gloves

Hand protection:

Wear protective gloves. Use barrier cream. Wash your hands

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of inadequate ventilation wear respiratory protection.

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke when using this product.

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Viscous liquid.
Color	: amber
Odor	: characteristic
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Density	: 1.0396 g/ml
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available

Elastic DL160 - Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, kinematic	: 913.813 mm ² /s
Viscosity, dynamic	: 950 (900 – 1000) mPa·s Viscosity @ 25°C (cPs)
Explosion limits	: No data available
Particle characteristics	: No data available

Proprietary (Photoinitiator)

Particle characteristics	No data available
--------------------------	-------------------

Proprietary (Crosslinking agent)

Particle characteristics	No data available
--------------------------	-------------------

Proprietary (Acrylate)

Particle characteristics	No data available
--------------------------	-------------------

Proprietary (Acrylate)

Particle characteristics	No data available
--------------------------	-------------------

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Protect from sunlight. Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Likely routes of exposure

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Elastic DL160 - Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proprietary (Photoinitiator)	
LD50 oral rat	> 2000 mg/kg body weight Animal: rat, Guideline: other:OECD GUIDELINE No.401 (CORRESPONDING TO 84/449/EEC, B.1)
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: other:OECD GUIDELINE No.402 (CORRESPONDING TO 84/449/EEC, B.3)
Proprietary (Crosslinking agent)	
LD50 oral rat	1000 – 2000 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LC50 Inhalation - Rat	> 3.363 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)
ATE US (oral)	1000 mg/kg body weight
Proprietary (Acrylate)	
LD50 dermal rabbit	> 3000 mg/kg body weight Animal: rabbit, Animal sex: male, Guideline: other:
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
Proprietary (Acrylate)	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Proprietary (Photoinitiator)	
NOAEL (oral,rat,90 days)	< 10.8 mg/kg body weight Animal: other:ALBINO RAT/Tif: RAIf (SPF) HYBRIDIS OF RII/1×RII/2, Guideline: other:EEC Directive, B.7
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Proprietary (Crosslinking agent)	
NOAEL (oral,rat,90 days)	≥ 100 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Elastic DL160 - Black	
Viscosity, kinematic	913.813 mm²/s
Proprietary (Photoinitiator)	
Viscosity, kinematic	No data available
Proprietary (Crosslinking agent)	
Viscosity, kinematic	No data available

Elastic DL160 - Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proprietary (Photoinitiator)	
Proprietary (Acrylate)	
Viscosity, kinematic	No data available
Proprietary (Acrylate)	
Viscosity, kinematic	No data available
Potential Adverse human health effects and symptoms	: Harmful if swallowed. May be harmful in contact with skin.
Symptoms/effects	: May be harmful if inhaled. May be harmful in contact with skin. May cause an allergic skin reaction.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: May cause slight irritation.
Symptoms/effects after ingestion	: May be harmful if swallowed.
Other information	: Likely routes of exposure: inhalation. Likely routes of exposure: ingestion, skin and eye.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment. Toxic to aquatic life with long lasting effects.
Ecology - water	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Proprietary (Photoinitiator)	
LC50 - Fish [1]	> 100 mg/l Test organisms (species): other:ZEBRA FISH
EC50 - Other aquatic organisms [1]	2.15 mg/l Test organisms (species): other aquatic crustacea:DM
Proprietary (Crosslinking agent)	
LC50 - Fish [1]	0.034 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 0.35 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 0.12 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
Proprietary (Acrylate)	
LC50 - Fish [1]	0.704 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 72h - Algae [1]	1.98 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	0.596 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
LOEC (chronic)	0.277 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.092 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

Elastic DL160 - Black	
Persistence and degradability	Not rapidly degradable

Elastic DL160 - Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proprietary (Photoinitiator)	
Persistence and degradability	Biodegradability in water: no data available.
Proprietary (Crosslinking agent)	
Persistence and degradability	Not rapidly degradable
Proprietary (Acrylate)	
Persistence and degradability	Not rapidly degradable
Proprietary (Acrylate)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Fluorinated greenhouse gases :
: No

SECTION 13 Disposal considerations

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Avoid release to the environment. Comply with applicable regulations for solid waste disposal. Dispose in a safe manner in accordance with local/national regulations.
Additional information : Clean up even minor leaks or spills if possible without unnecessary risk. Consult an expert on waste disposal or treatment. Flammable vapors may accumulate in the container.
Ecological waste information : Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

UN-No.(DOT) : Not applicable
UN-No. (TDG) : Not applicable
UN-No. (IMDG) : 3082
UN-No. (IATA) : 3082

14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Not applicable
Proper Shipping Name (TDG) : Not applicable
Proper Shipping Name (IMDG) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Proper Shipping Name (IATA) : Environmentally hazardous substance, liquid, n.o.s.

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : Not applicable

Elastic DL160 - Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TDG

Transport hazard class(es) (TDG) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : 9

Hazard labels (IMDG) : 9



IATA

Transport hazard class(es) (IATA) : 9

Hazard labels (IATA) : 9



14.4. Packing group

Packing group (DOT) : Not applicable

Packing group (TDG) : Not applicable

Packing group (IMDG) : III

Packing group (IATA) : III

14.5. Environmental hazards

Dangerous for the environment : Yes

Marine pollutant : Yes



Other information : No supplementary information available.

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT

Not applicable

TDG

Not applicable

IMDG

Special provision (IMDG) : 274, 335, 969

Limited quantities (IMDG) : 5 L

Excepted quantities (IMDG) : E1

Packing instructions (IMDG) : LP01, P001

Packing provisions (IMDG) : PP1

IBC packing instructions (IMDG) : IBC03

Tank instructions (IMDG) : T4

Tank special provisions (IMDG) : TP1, TP29

EmS-No. (Fire) : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE

EmS-No. (Spillage) : S-F - SPILLAGE SCHEDULE Foxtrot - WATER-SOLUBLE MARINE POLLUTANTS

Elastic DL160 - Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Stowage category (IMDG) : A

IATA

Special provision (IATA) : A97, A158, A197, A215
PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y964
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 964
PCA max net quantity (IATA) : 450L
CAO packing instructions (IATA) : 964
CAO max net quantity (IATA) : 450L
ERG code (IATA) : 9L

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Proprietary (Photoinitiator)

Listed on the Canadian NDSL (Non-Domestic Substances List)

Proprietary (Crosslinking agent)

Listed on the Canadian DSL (Domestic Substances List)

Proprietary (Acrylate)

Listed on the Canadian DSL (Domestic Substances List)

Proprietary (Acrylate)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Proprietary (Acrylate)


Listed on IARC (International Agency for Research on Cancer)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

Elastic DL160 - Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. State regulations

 **WARNING:** This product can expose you to Proprietary (Acrylate), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16 Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 17/04/2025

Issue date : 14/02/2022

Full text of hazard classes and H-statements

H302	Harmful if swallowed
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

Abbreviations and acronyms

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration

Elastic DL160 - Black

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Abbreviations and acronyms	
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

SDS US (GHS HazCom 2012) No CAS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.